

ERGO Serie

Hoch-Frequenz Vibriernadeln
Aiguilles haute-fréquence
Aghi vibranti di alta frequenza



Modell Modèle Modello	Art. Nr No. Art.	Gewicht Poids Peso kg	Volt/Hz	Schlauch- länge, Longueur Longhezza m	Amp. A	Leistung Puissance Potenza W	Kapazität Capacité Capacità m ³ /h	Dreh- zahl, RPM	Vibrations- kraft, Force Centrifuge, Forza centrifuga, N	Ø- mm	Wirkungs- kreis, Ø-d'action Ø-azione cm
ERGO Turbo 38	VIP10.375	12	42/200	1	6	510	20	1200	1700	38	32
ERGO Turbo 42	VIP10.376	13			6	560	25		2400	42	36
ERGO Turbo 52	VIP10.359	15			10	800	40		3800	52	42
ERGO Turbo 58	VIP10.360	16			11	900	45		5500	58	46
ERGO Turbo 65	VIP10.361	18			13	980	50		7200	65	52
ERGO Turbo 52RC	VIP10.363	15			10	800	40		3800	52	42
ERGO Turbo 58RC	VIP10.364	16			11	900	45		5500	58	46
ERGO Turbo 65RC	VIP10.365	18			13	980	50		7200	65	52

RC = Gummikopf, Tête en caoutchouc, Testa in gomma

TECHNISCHE DATEN SIND LABORWERTE

Verlängerungskabel Câble de rallonge Cavo di prolunga	Volt	Art. Nr No. Art.
15m	42 Volt	VIP25.500.15
20m	42 Volt	VIP25.500.20

